



AEGIS

Autonomous Engineering & Governance Intelligence System

Deterministic Governance for Autonomous AI Agents in Enterprise Operations

“AI proposes and reasons. Deterministic software controls and verifies.”

Architecture · Policy Engine · Agent Governance · Sandboxed MCP Execution · Chaos Engineering

EXECUTIVE SUMMARY

Enterprises are moving from AI assistants that *answer* to AI agents that *act*: reading repositories, editing code, querying databases, and operating infrastructure. The reasoning capability that makes these agents useful is probabilistic by nature, and probabilistic systems cannot be the final authority over production systems. **AEGIS** resolves this tension with one architectural rule: AI proposes and reasons; deterministic software controls and verifies.

AEGIS coordinates eight specialised agents through a code-enforced mission state machine. Every tool call crosses a deterministic policy engine that scores risk from 0 to 100; DESTRUCTIVE and DEPLOY actions are forced to CRITICAL and held for human approval. Agents reach infrastructure only through a typed Model Context Protocol (MCP) gateway, and no agent can certify its own work: an independent Verifier re-runs the evidence. Across 16 benchmark runs the pipeline achieved 100% root-cause selection, 100% security-review pass, 100% independent-verification pass, and **zero unsafe actions**, at a mean pipeline duration of approximately 0.57 ms of control-plane time.

8 governed agents	5 typed MCP servers	0–100 dynamic risk score	0 unsafe actions / 16 runs	~0.57 ms mean pipeline time
----------------------	------------------------	-----------------------------	-------------------------------	--------------------------------

Abstract

Autonomous AI agents promise to compress the incident-to-remediation loop from hours to seconds, but granting a large language model unrestricted authority over shells, databases, and deployment pipelines converts every hallucination, prompt injection, and poisoned memory into a potential production outage or security breach. Probabilistic reasoning is an excellent source of *hypotheses* and a dangerous source of *authority*. This paper presents AEGIS, a governance-first multi-agent system for incident response and software remediation built on FastAPI, Pydantic v2, asynchronous SQLAlchemy 2.0, PostgreSQL, and React 19. AEGIS separates *proposal* from *execution*: eight agents with explicit “CANNOT” boundaries generate observations, hypotheses, and patches, while a deterministic policy engine intercepts every tool call, a code-enforced state machine governs mission progress, a typed MCP gateway removes shell access entirely, ephemeral Docker sandboxes confine execution, an independent Verifier re-derives every claim, and a human-in-the-loop gate blocks all destructive or deploy-class actions. We describe the architecture, the policy and risk model, the sandbox execution profile, and a chaos-engineering and benchmark programme that, over 16 scripted runs, produced 100% root-cause selection, security review, and independent verification with zero unsafe actions.

Contents

Abstract

2

1. Introduction & the Core Philosophy

4

1.1 The authority problem in agentic systems

4

1.2 The separation principle

4

1.3 Design tenets

4

1.4 Threat model and control mapping

4

2. System Architecture

5

2.1 Technology stack

5

2.2 FastAPI backend

6

2.3 Data layer: asynchronous SQLAlchemy 2.0 on PostgreSQL

6

2.4 The PostgreSQL-backed event bus

7

2.5 Server-Sent Events streaming to the React frontend

7

2.6 The code-enforced mission state machine

7

2.7 Observable memory with quarantine

8

2.8 Observability

8

3. The A2A Agent Roster

8

3.1 The incident-to-resolution workflow

8

3.2 Agent roster and strict boundaries

8

3.3 Structured outputs and separation of duties

9

4. The Deterministic Policy Engine

9

4.1 Interception of every tool call

10

4.2 Dynamic risk scoring and risk bands

10

4.3 Fail-closed semantics

10

4.4 Reference implementation of the policy check

10

4.5 The human approval gate

11

4.6 Defence in depth

12

5. Sandboxed MCP Execution

12

5.1 The MCP gateway: typed tools, no shell

12

5.2 Ephemeral Docker containers with cgroup limits

13

5.3 From sandbox output to trusted verdict

13

6. Chaos Engineering & Benchmarks

13

6.1 The Chaos Lab

13

6.2 Red-team validation of the guards

14

6.3 Benchmark methodology

14

6.4 Interpreting the results responsibly

15

Conclusion

15

Appendix A: API Surface

16

Appendix B: Glossary

16

1. Introduction & the Core Philosophy

1.1 The authority problem in agentic systems

A language model is a function from context to a *distribution* over text. Sampling from that distribution is what makes models creative, and it is also why no prompt, fine-tune, or system message can make their behaviour *guaranteed*. When an agent is wired directly to a shell, a database connection, or a deployment API, the model's output stops being advice and becomes an action. The failure modes are well understood and compound in multi-agent topologies: confident but wrong root-cause analysis; patches that touch secrets or escape their working directory; instructions smuggled into logs, tickets, or retrieved documents (indirect prompt injection); “memory poisoning” that persists an attacker's instruction across sessions; and *self-certification*, where the agent that wrote a fix also declares it working.

The industry response has largely been to make prompts longer and guardrails “smarter”, that is, to use another probabilistic component to police the first. This lowers incident rates without changing their *worst-case* bound, and it makes the system impossible to audit by inspection: the reason an action was allowed is, ultimately, a sampled token. Enterprise change management, SOX/ISO-27001-style controls, and incident post-mortems all require the opposite property: a decision procedure whose outcome can be derived from its inputs, replayed, and explained.

1.2 The separation principle

Principle. AI proposes and reasons. Deterministic software controls and verifies. Models are confined to the generation of *structured proposals* (hypotheses, patches, plans). Every transition from proposal to effect is mediated by code that is typed, versioned, testable, and replayable.

AEGIS treats the model as an untrusted but valuable *advisor*. Its outputs are parsed into strict schemas and discarded if malformed; its tool requests are authorised by a policy engine it cannot modify; its claims of success are never accepted without independent re-execution; and its most dangerous requests are routed to a human. The result is a system in which the *blast radius* of any single model error is bounded by construction rather than by hope.

1.3 Design tenets

- **Deterministic control.** Authorisation, state transitions, severity mapping, verdicts, and retrieval scoring are pure functions of their inputs. Given the same inputs, AEGIS makes the same decision.
- **Least privilege by role.** Each agent has a narrow capability set and an explicit list of things it *cannot* do. Capabilities are published as discoverable A2A agent cards.
- **Fail closed.** Unknown tools, malformed model output, empty verification suites, protected paths, and ambiguous states resolve to denial, failure, or ERROR, never to silent success.
- **Independent verification.** The party that proposes a change is never the party that certifies it. The Verifier executes checks itself and ignores the Coder's assertions.
- **Human accountability for irreversible actions.** Destructive and deploy-class actions are forced to CRITICAL and cannot proceed without a recorded human decision bound to an authenticated identity and a policy version.
- **Observable by construction.** Every state change, tool call, and approval is committed to an append-only PostgreSQL event log before any subscriber is notified, and missions can be replayed read-only.
- **Provider-agnostic reasoning.** The control plane is independent of the model behind it; scripted, local (Ollama), and routed providers share one interface, so governance can be tested with no model at all.

1.4 Threat model and control mapping

AEGIS assumes that any model output and any data ingested by an agent (logs, tickets, memory, documents) may be adversarial or simply wrong. Table 1 maps the principal threat classes to the deterministic controls that contain them.

Threat	Representative attack or failure	Primary control	Enforcing component
Prompt injection / memory poisoning	Log line instructs the agent to “ignore previous instructions” and delete data	Pattern screening, quarantine flag excludes record from retrieval	SecurityAgent.review_memory, MemoryStore

Threat	Representative attack or failure	Primary control	Enforcing component
Path traversal / sandbox escape	Patch or tool writes to <code>../../../../etc/passwd</code>	Root-confined filesystem server raises <code>PermissionError</code> ; path validation on every <code>FilePatch</code>	Filesystem MCP, <code>FilePatch</code> , <code>SecurityAgent</code>
Tool abuse / privilege escalation	Agent requests an unregistered or destructive tool (e.g. <code>rm_rf_root</code>)	Fail-closed tool registry; risk scoring; forced CRITICAL	<code>PolicyEngine</code> , <code>PolicyGuard</code>
Secret exfiltration	Patch targets credentials or key material	Protected-path pattern list rejects the whole proposal	<code>SecurityAgent.review_patch</code>
Self-certification	Coder reports “tests pass” without evidence	Verifier runs checks itself; PASSED only if all checks pass; zero checks → ERROR	<code>VerifierAgent</code> , <code>VerificationReport</code>
Unauthorised progress	Agent skips investigation or approval	Code-enforced state machine; only defined transitions are legal	<code>MissionState</code> , <code>MissionRepository</code>
Unreviewed irreversible change	Deploy or delete executes automatically	Human-in-the-loop gate; Approval record with identity and policy version	Approvals API, Approval model
Unbounded resource use	Runaway concurrent model or tool calls	Concurrency limits on AI calls and tool calls	<code>ResourceGovernor</code>
Repudiation	“Who allowed this?”	Immutable event log written before notification; mission replay	<code>EventBus</code> , Event model, <code>Replay API</code>

Table 1. Threat classes and the deterministic controls that contain them.

2. System Architecture

AEGIS is a layered system in which every layer that touches the outside world is deterministic, and the only probabilistic component, the model provider, sits behind a narrow, schema-validated interface. Figure 1 shows the logical architecture; the sections that follow describe each layer.

2.1 Technology stack

Layer	Technology	Role in AEGIS
Runtime	Python 3.14	Async-first control plane; structural typing and dataclasses for agent contracts
API	FastAPI, Uvicorn	Application factory, dependency injection, REST endpoints, SSE streaming
Validation	Pydantic v2, pydantic-settings	Typed request/response schemas, constrained fields, MCP tool parameter schemas, configuration
Persistence	SQLAlchemy 2.0 (async), asyncpg, PostgreSQL	Missions, incidents, approvals, tool calls, agents, immutable event log (JSONB payloads)
Frontend	React 19, Vite, TypeScript, Tailwind CSS 4, React Router 7	Operator console: Chaos Lab, incident detail, approvals, verification, benchmarks, audit log
Sandboxing	Docker (Linux cgroups)	Ephemeral, resource-limited containers for code and test execution
Observability	OpenTelemetry, correlation IDs, metrics endpoint	Distributed tracing, request correlation, execution-trace spans per mission
Security	JWT bearer tokens, bcrypt, role-based project membership	Authenticated operators; owner / maintainer / viewer roles per project

Table 2. AEGIS technology stack.




Figure 1. Logical architecture. Only the agent layer is probabilistic; every path to infrastructure crosses the control plane and a typed MCP server.

2.2 FastAPI backend

The backend is assembled by an **application factory** (`create_app`) that wires every collaborator onto `app.state` exactly once: the **ResourceGovernor** (bounded concurrency for AI calls and tool calls), the durable **EventBus**, the **ToolRegistry** and **McpGateway**, the agent runtime, the **A2A gateway** seeded with the eight agent cards, the **MemoryStore**, and a **MetricsCollector**. Sixteen routers (auth, projects, environments, memberships, missions, incidents, approvals, chaos, tools, red team, A2A, memory, policies, benchmarks, replay, updates) are mounted behind explicit prefixes; Appendix A lists the full surface.

Request handling is deliberately boring. **Pydantic v2** models with constrained fields (for example, passwords of 8–128 characters and bounded string lengths) reject malformed input before it reaches business logic. Identity is a bearer JWT verified by a shared dependency that resolves the user record on every request; passwords are stored as bcrypt hashes. A **correlation-ID middleware** stamps every request and log line, and a typed `AegisError` hierarchy (validation, not-found, internal) maps to a uniform JSON error envelope, while a catch-all handler logs the full traceback server-side and returns a safe, non-leaking 500. Liveness (`/health/live`) and readiness (`/health/ready`, which probes the database, model provider, and agent runtime and returns 503 when degraded) are separate endpoints for orchestrators.

2.3 Data layer: asynchronous SQLAlchemy 2.0 on PostgreSQL

All persistence uses SQLAlchemy 2.0's typed `Mapped[]` declarative style over **asyncpg**, with `pool_pre_ping` enabled and sessions created with `expire_on_commit=False`. Primary keys are UUIDv4 and every mutable table carries server-side `created_at/updated_at` timestamps through shared mixins. Enumerations (mission state, incident severity, tool-call state, approval status) are persisted as constrained strings rather than native database enums, so state vocabularies evolve through migrations (Alembic) without `ALTER TYPE` hazards. Semi-structured artefacts (investigation results, remediation plans, mission context, tool-call arguments and results) are stored as **JSONB**.

Entity	Purpose	Key attributes
Incident	A detected anomaly or failure	severity (low → critical), status (detected, investigating, remediating, resolved, false_positive), investigation and remediation JSONB
Mission	An orchestrated unit of work to resolve an incident	state (10-state machine), objective, project and incident foreign keys, context JSONB

Entity	Purpose	Key attributes
Agent / AgentTask	Registered agent identity and its units of work within a mission	agent state (idle...awaiting_approval, verifying, failed), task state (pending → completed/failed/cancelled), result JSONB
ToolCall	One governed invocation of a tool by an agent	state: requested → approved/rejected → executing → completed/failed; arguments, result, error_message
Approval	Human (or policy) authorisation record for a gated action	action_type, action_payload, risk_level, reason, status, policy_version, approved_by (user FK)
Event	Immutable audit/event-bus record	timestamp, event_type, actor, project_id, payload JSONB; indexed on timestamp, type, actor, project
Project / Environment / Membership	Tenancy, deployment targets, RBAC	environment kind (development, staging, production); role (owner, maintainer, viewer); unique (user, project)

Table 3. Core persistence model.

2.4 The PostgreSQL-backed event bus

The event bus is the system's spine and its audit trail. Its defining property is **durability before delivery**: `EventBus.publish()` first commits an Event row to PostgreSQL, then invokes registered async handlers, then fans the event out to every attached in-memory stream queue. Because the commit precedes notification, a crashing or slow subscriber can never erase the audit record, and the log is the source of truth from which any UI state can be reconstructed. Typed `EventType` values (for example `incident.created`, `approval.requested`, `approval.granted`, `approval.rejected`, `mission.state_changed`) carry a JSONB payload and the acting identity, so the question “who or what changed this mission, and when?” is answerable with a single indexed query. A read-only **replay** endpoint assembles a mission, its incident, its approval, and its ordered events into a snapshot for post-incident review.


2.5 Server-Sent Events streaming to the React frontend

Operator consoles need to see agents work in real time without polling. AEGIS exposes `GET /updates/stream`, an authenticated **Server-Sent Events** endpoint. On connect, the server attaches a dedicated `asyncio.Queue` to the event bus and emits a ping event. It then streams each published event using native SSE framing (`event: <type> / data: <json>`), and if no event arrives within 15 seconds it emits a heartbeat to keep intermediaries from closing the connection. On client disconnect the generator's `finally` clause detaches the queue, so abandoned connections do not leak memory.

Because the browser's built-in `EventSource` cannot set an `Authorization` header, the React client consumes the stream with `fetch()`, a bearer token, and a `ReadableStream` reader with an `AbortController` for teardown. The Audit Log page renders a live connection indicator and an event table; the console is built with React 19, Vite, TypeScript, Tailwind CSS 4, and React Router 7, with a command palette for operator navigation.

2.6 The code-enforced mission state machine

A **Mission** is the unit of governed work. Its lifecycle is an explicit enumeration, `MissionState`, mutated only through repository methods invoked by the Incident Commander or by the approval API. The canonical path is `CREATED` → `INVESTIGATING` → `REMEDIATION_PLANNED` → `REMEDIATION_RUNNING` → `VERIFYING` → `AWAITING_APPROVAL` → `RESOLVED`, with `QUEUED`, `REMEDIATION_RUNNING`, and `VERIFYING` as intermediate execution states, and `FAILED` and `CANCELLED` as terminal states reachable from any active state.



Illegal transitions are impossible by construction: only the Commander and the approval API call `update_state`; agents have no write path to mission state.

Any active state may fall to **FAILED** (e.g. no root cause above the confidence floor) or **CANCELLED** (operator).

Figure 2. Mission state machine. Solid arrows are the happy path; **FAILED** and **CANCELLED** are terminal.

The Commander enforces the investigation fork deterministically: it opens the mission, delegates hypothesis generation, and asks the Investigator to select a root cause. If no hypothesis meets the **confidence floor**, the mission transitions to FAILED; otherwise to REMEDIATION_PLANNED. Human rejection of an approval sets the mission to FAILED and returns the incident to DETECTED; approval sets both to RESOLVED. The same discipline governs inter-agent work: A2A tasks follow a transition table (SUBMITTED → WORKING → COMPLETED | FAILED | CANCELED) in which terminal states have *no outgoing edges*, and an invalid move raises an exception rather than being coerced.

2.7 Observable memory with quarantine

AEGIS provides four memory classes: **working** (current mission state), **episodic** (prior incidents), **semantic** (known facts about systems), and **procedural** (proven remediation workflows). Retrieval is intentionally **not** an opaque embedding lookup: relevance is computed by deterministic keyword overlap, and every `RetrievalResult` exposes the record id, type, relevance score, source, and the reason it was retrieved. Records carry a quarantined flag; content that trips the Security agent's injection screen is stored quarantined and is excluded from retrieval, so poisoned memory cannot influence later reasoning while remaining available for forensic review.


2.8 Observability

Beyond the event log, AEGIS emits OpenTelemetry traces and correlates them with request-scoped correlation IDs; execution-trace spans model the mission as a graph of agent and tool activity. A `/metrics` endpoint exposes collected application metrics, and a per-agent **vitals** endpoint reports current task, running/idle status, missions in the last seven days, tool-call volume, success rate (completed / (completed + failed)), and failure count. Every governed tool call is archived with its state history in the Tool Calls area of the console.

3. The A2A Agent Roster

AEGIS uses an **Agent-to-Agent (A2A)** model in which each agent publishes an **agent card** (a name such as `verifier.aegis`, a description, a list of capabilities, and skills) to a registry. Discovery is deterministic: results are always sorted by agent name, so delegation decisions do not vary with registration order. Work is exchanged as structured `A2AMessage` and `A2ATask` objects with the validated transition table described in §2.6. Agent cards are public discovery metadata and are served unauthenticated; agent vitals and all mutating endpoints require a token.

3.1 The incident-to-resolution workflow



■ LLM-assisted proposal (output schema-validated)

□ Deterministic logic

■ Human decision (identity + policy version)

Figure 3. End-to-end workflow with mission states. Probabilistic reasoning appears only in two roles and is always followed by deterministic review.

3.2 Agent roster and strict boundaries

Eight agents form the roster. Each has a narrow purpose, a published capability list, and an explicit set of actions it is structurally unable to perform. These boundaries are enforced by what each agent is *given*: for example, the Commander holds a repository handle and no tool executor; the Verifier receives check callables and no write tool.

Agent (card)	Role and capabilities	CANNOT (strict boundary)	Nature
Observer observer.aegis	Evaluates signals against fixed thresholds (CPU 90%, memory 95%, error rate 5%, latency 2,000 ms); maps signal type to incident severity; emits structured Observations and files an Incident for anomalies.	Modify the observed system; write to mission, approval, or tool-call state; open missions; invoke write or execute tools; treat normal readings as incidents.	Deterministic
Incident Commander incident-commander.aegis	Opens the mission (CREATED → INVESTIGATING), delegates investigation, advances the state machine, marks FAILED, requests approval, resolves after verification.	Execute tools or modify systems; generate hypotheses itself; grant itself authority; bypass the policy engine or approval gate; skip states.	Deterministic
Investigator investigator.aegis	Generates ranked root-cause hypotheses as strict JSON (claim, confidence 0–1, evidence, counter-evidence) from logs, metrics, git, database and test evidence.	Write files, database rows, or state; execute commands; return unstructured or schema-invalid output; select a root cause below the confidence floor.	LLM + validator
Coder coder.aegis	Proposes a PatchProposal (list of FilePatch); applies only validated patches through the Filesystem MCP server inside the sandbox.	Merge or mark anything resolved without Verifier sign-off; write outside the confined root; touch protected or secret paths; push to protected branches; deploy.	LLM + validator
Security security.aegis	Reviews tool requests (via PolicyGuard), patches (path validation plus protected-pattern screen), and memory content (injection screen with quarantine). Fail-closed.	Author patches; weaken or waive policy; waive human approval; allow when any path is suspicious.	Deterministic
Verifier verifier.aegis	Runs every check itself and builds a VerificationReport: PASSED only if all checks pass, FAILED otherwise, ERROR when nothing could be verified.	Trust the Coder's claims; modify the code under test; report PASSED on an empty suite; resolve missions.	Deterministic
Researcher researcher.aegis	Retrieves documentation and produces source-backed findings that feed hypothesis generation.	Mutate any system or state; emit findings without sources; call write, execute, or deploy tools.	LLM + validator
Red Team red-team.aegis	Attacks AEGIS itself (prompt injection, path traversal, tool abuse, destructive requests) against the live guards in a throw-away temporary directory and reports expected vs. actual.	Attack external or production targets; persist artefacts outside its temporary root; alter mission or policy state.	Deterministic

Table 4. The AEGIS agent roster. “LLM + validator” agents may use a model, but their outputs are parsed and validated deterministically before use.

3.3 Structured outputs and separation of duties

Model-facing agents are prompted to return *only* a JSON object of a fixed shape. The surrounding code parses the response into typed dataclasses (Hypothesis with a bounded confidence, Evidence typed as log, metric, git, database, or test; PatchProposal with per-file validation) and silently discards anything that does not conform. Because the BaseLLMProvider interface is the only place a model is invoked, AEGIS ships interchangeable providers: a mock provider for development, a **scripted** provider that replays deterministic responses for governance testing and benchmarks, a local **Ollama** provider, and a model router.

The roster enforces four distinct duties on every remediation, and no single agent holds more than one:

- **Proposer** (Investigator, Coder): generates hypotheses and patches, with no execution authority.
- **Reviewer** (Security): applies deterministic policy to what was proposed, with no authoring authority.
- **Verifier** (Verifier): independently re-establishes the facts, with no write authority.
- **Approver** (human operator): the only principal that can authorise an irreversible effect, recorded with identity and policy version.

4. The Deterministic Policy Engine

The policy engine is the single point through which authority flows. It is a pure, versioned function from an *action* and its *context* to a PolicyDecision, a frozen (immutable) record containing whether the action is allowed, whether it requires

human approval, and the reason. It has no model dependency, no network access, and no hidden state, so the same request always produces the same decision and every decision can be unit-tested, replayed, and explained.

4.1 Interception of every tool call

Tools are never invoked directly. A request creates a `ToolCall` row in state `REQUESTED`; the `ToolExecutionService` then asks the `PolicyGuard` to `assert_allowed` the tool. Three outcomes are possible: **(a)** a `PermissionError` marks the call `FAILED` with `policy_blocked: <reason>` and the tool is never entered; **(b)** an `ApprovalRequiredError` holds the call pending a human decision; **(c)** the call proceeds to `EXECUTING` and finally `COMPLETED` or `FAILED`. Each state change is persisted, so blocked and held attempts are as visible in the audit trail as successful ones.

4.2 Dynamic risk scoring and risk bands

Every action category carries a **baseline score**; the engine adjusts it by context (for example, the target environment, whether the target is a protected resource such as the main branch, and the sensitivity of the path) to produce an integer in `[0, 100]`, which is mapped to a risk band. Tools are registered in a `TOOL_CATEGORIES` table that binds each tool name to an action category. Two categories are special: `DESTRUCTIVE` and `DEPLOY` are **forced to CRITICAL regardless of score or context** and are blocked pending human-in-the-loop approval. No amount of favourable context can lower them, and no agent can reclassify a tool.

Risk band	Score	Default disposition	Typical actions
SAFE	0–20	Execute automatically; log	Read-only inspection (e.g. <code>git_status</code> , file reads)
LOW	21–40	Execute automatically; log with context	Non-mutating queries, diagnostics in development
MEDIUM	41–60	Execute after Security-agent review	Sandboxed writes and test execution
HIGH	61–80	Held for human approval (Approval record created)	Applying a verified patch to a real environment
CRITICAL	81–100	Blocked; requires human-in-the-loop approval	All <code>DESTRUCTIVE</code> and <code>DEPLOY</code> actions (forced)

Table 5. Risk bands and default dispositions.

4.3 Fail-closed semantics

A tool name that is not present in the registry is not “low risk”; it is *denied*. The built-in red-team suite verifies this by requesting a fabricated `rm_rf_root` tool and asserting that the engine returns `allowed=False`. The same posture applies elsewhere: a patch proposal is rejected in its entirety if any path fails validation or matches a protected pattern; an empty verification suite yields `ERROR`, not `PASSED`; and a mission with no root cause above the confidence floor `FAILED`s rather than guessing.

4.4 Reference implementation of the policy check

Listing 1 condenses the decision procedure. The data shapes and the guard’s control flow mirror the production interfaces (`PolicyDecision`, `evaluate_tool`, `assert_allowed`); numeric constants are representative and are versioned in deployment.

```

from dataclasses import dataclass
from enum import Enum

class ActionCategory(str, Enum):
    READ = "read"; WRITE = "write"; EXECUTE = "execute"
    DESTRUCTIVE = "destructive"; DEPLOY = "deploy"

class RiskLevel(str, Enum):
    SAFE = "safe"; LOW = "low"; MEDIUM = "medium"; HIGH = "high"; CRITICAL = "critical"

BASELINE_SCORE = {ActionCategory.READ: 10, ActionCategory.WRITE: 45, ActionCategory.EXECUTE: 55,
                   ActionCategory.DESTRUCTIVE: 95, ActionCategory.DEPLOY: 90}
ENV_MODIFIER = {"development": 0, "staging": 10, "production": 20}
FORCED_CRITICAL = {ActionCategory.DESTRUCTIVE, ActionCategory.DEPLOY}
TOOL_CATEGORIES = {"git_status": ActionCategory.READ, "write_file": ActionCategory.WRITE,
                   "run_tests": ActionCategory.EXECUTE}          # anything not listed is unknown

@dataclass(frozen=True)                                # immutable: a decision cannot be edited after the fact
class PolicyDecision:
    allowed: bool
    risk_score: int
    risk_level: RiskLevel
    requires_human_approval: bool
    reason: str

def _band(score: int) -> RiskLevel:
    return (RiskLevel.SAFE if score <= 20 else RiskLevel.LOW if score <= 40 else
            RiskLevel.MEDIUM if score <= 60 else RiskLevel.HIGH if score <= 80 else RiskLevel.CRITICAL)

class PolicyEngine:
    def decide(self, cat: ActionCategory, env: str = "development", protected: bool = False) -> PolicyDecision:
        score = min(100, BASELINE_SCORE[cat] + ENV_MODIFIER[env] + (15 if protected else 0))
        if cat in FORCED_CRITICAL:                        # DESTRUCTIVE / DEPLOY: context cannot lower this
            score, level = max(score, 81), RiskLevel.CRITICAL
        else:
            level = _band(score)
        gated = level in (RiskLevel.HIGH, RiskLevel.CRITICAL)
        return PolicyDecision(True, score, level, gated, f"{cat.value} scored {score} ({level.value})")

    def evaluate_tool(self, tool: str, **ctx) -> PolicyDecision:
        cat = TOOL_CATEGORIES.get(tool)
        if cat is None:                                  # fail closed on unknown tools
            return PolicyDecision(False, 100, RiskLevel.CRITICAL, False, f"unknown tool: {tool}")
        return self.decide(cat, **ctx)

class PolicyGuard:
    def __init__(self, policy: PolicyEngine | None = None):
        self._policy = policy or PolicyEngine()

    def assert_allowed(self, tool: str, **ctx) -> PolicyDecision:
        decision = self._policy.evaluate_tool(tool, **ctx)
        if not decision.allowed:
            raise PermissionError(decision.reason)        # -> ToolCall FAILED "policy_blocked"
        if decision.requires_human_approval:
            raise ApprovalRequiredError(decision.reason)  # -> held for HITL Approval record
        return decision                                  # -> EXECUTING

# policy.evaluate_tool("git_status")          -> SAFE (10), executes
# policy.evaluate_tool("write_file", env="production") -> 65 HIGH, requires approval
# policy.decide(ActionCategory.DEPLOY)        -> CRITICAL (>=81), blocked pending human approval
# policy.evaluate_tool("rm_rf_root")          -> allowed=False, PermissionError (fail closed)

```

Listing 1. Deterministic policy decision and guard (condensed reference implementation).

4.5 The human approval gate

When a remediation reaches `AWAITING_APPROVAL`, AEGIS persists an **Approval** record binding the mission and incident to the *action type*, a serialised *payload* (the affected file paths), the *risk level*, the reason, and the **policy version** in force (for example `policy-v1`), and publishes an `approval.requested` event. The operator console surfaces the pending approval alongside the Security verdict and the Verifier's independent results.

The decision endpoint is intentionally narrow:

- Authenticated operators only; the approving principal is taken from the verified JWT, never from the request body, and stored as `approved_by`.
- Only approved or rejected are accepted; a decision is accepted only while the record is PENDING, making each approval a single-use, non-repeatable event.
- **Approved:** mission → RESOLVED, incident → RESOLVED. **Rejected:** mission → FAILED, incident returns to DETECTED.
- State changes are committed first (scalars are captured before commit because async sessions expire loaded objects), then `mission.state_changed` and `approval.granted/approval.rejected` events are published with the operator's identity.

4.6 Defence in depth

#	Layer	Mechanism	Failure it prevents
1	Schema validation	Pydantic v2 constrained models; strict agent JSON contracts	Malformed or oversized input; unstructured model output
2	Policy engine + guard	Risk score, TOOL_CATEGORIES, forced CRITICAL, fail-closed	Unauthorised, unknown, or destructive tool use
3	Security agent	FilePatch path validation, protected-pattern screen, memory-injection screen	Secret access, traversal, poisoned context
4	MCP server confinement	Root-confined filesystem, protected git branches, typed parameters	Writes outside the workspace; pushes to main
5	Sandbox	Ephemeral container with cgroup limits and timeouts	Resource exhaustion; host compromise
6	Independent Verifier	Self-executed checks; strict PASSED semantics	False success claims; regressions
7	Human-in-the-loop	Approval record with identity and policy version	Unreviewed irreversible change
8	Event log + replay	Durable-before-delivery events; read-only mission replay	Repudiation; unexplainable decisions

Table 6. Eight independent layers; a single model failure must defeat all of them to cause harm.

5. Sandboxed MCP Execution

5.1 The MCP gateway: typed tools, no shell


Agents do not receive a terminal. They receive a **catalogue of typed tools** exposed through a Model Context Protocol (MCP) gateway. At start-up, five MCP servers are registered into the `ToolRegistry` via `McpGateway.register_server()`; each tool declares a name, a description, and a **Pydantic parameter schema**, and the registry exports these schemas for the model and for the authenticated `/tools` catalogue. Because arguments are validated objects rather than command strings, there is no shell-metacharacter injection surface, and because the catalogue is closed, a capability that is not registered does not exist for the agent. Execution of every registered tool remains policy-gated (§4.1).

MCP server	Representative tools	Built-in safeguards
Filesystem	<code>read_file</code> , <code>write_file</code> , <code>list_files</code> (typed path and content parameters)	Confined to a configured root; any resolved path outside it raises <code>PermissionError</code> (traversal such as <code>.././../etc/passwd</code> is blocked); validated again by the <code>Coder</code> before write (defence in depth)
Git	<code>git_status</code> , <code>diff</code> , <code>branch</code> and <code>commit</code> operations	<code>protected_branches={"main"}:</code> no direct mutation of protected branches; read-only calls such as <code>git_status</code> are SAFE-band
Docker	Run and inspect ephemeral containers	Executes work inside resource-limited, short-lived containers (§5.2); governed by the policy engine
Database	Typed, session-scoped queries via the async session factory	No raw connection exposure; typed operations; mutating actions are risk-scored and gated
Testing	<code>run_tests</code> (pytest) with structured results	Runs with a hard timeout (timeout kills the run and raises); output parsed into passed/failed counts; <code>success = failed==0</code> and <code>returncode==0</code>

Table 7. The five MCP servers and their safeguards.

5.2 Ephemeral Docker containers with cgroup limits

Anything that executes code, whether a candidate patch under test or a regression suite, runs in an **ephemeral Docker container** and never on the host or in the control-plane process. The container is created for one task, is bounded by Linux **control groups (cgroups)** for CPU, memory, and process count, receives only the files it needs, returns a *structured* result, and is destroyed. Nothing persists between runs, so state cannot leak from one mission to the next, and a malicious or buggy payload can at worst exhaust its own quota.



Sandbox boundary: nothing crosses back except the structured result; the Verifier derives its verdict from that result, not from the Coder's narrative.

Figure 4. Ephemeral container lifecycle.

Table 7 lists the reference execution profile applied to sandboxed runs. cgroup limits are the primary containment control; the remaining items reduce the attack surface further.

Control	Mechanism	Purpose
Memory limit	cgroup memory controller (hard cap, OOM-kill inside the container)	Bounds heap growth; a leak or fork-bomb cannot starve the host
CPU quota	cgroup CPU controller (shares / quota)	Prevents a busy-loop from monopolising cores
Process cap	cgroup PIDs controller	Contains fork bombs
Wall-clock timeout	Supervisor kills the container at the deadline; result is an error, not a pass	Bounds runtime of hanging tests
Ephemerality	One container per task, removed on completion	No cross-mission state or credential residue
Isolation profile	No privileged mode, no host socket mounts, non-root user, workspace-only mounts, network disabled by default	Removes host-escape and exfiltration paths
Structured I/O	Typed arguments in; exit code and parsed counts out	No free-form shell channel for injection

Table 8. Reference sandbox execution profile (resource limits are cgroup-enforced; exact values are deployment configuration).

5.3 From sandbox output to trusted verdict

Sandbox output is data, not authority. The Testing server parses pytest output into counts and returns {passed, failed, success, returncode, output}; the Verifier wraps each check as a callable (synchronous or asynchronous), executes it, and tallies outcomes. A check that raises or returns a falsy value counts as a failure. The report's ok property is true only if the status is PASSED, there are zero failed checks, and every check passed. In the Chaos Lab pipeline, patches are applied inside a confined sandbox root only after the Security review allows them, and the mission still stops at AWAITING_APPROVAL: sandbox success is a prerequisite for human review, never a substitute for it.

6. Chaos Engineering & Benchmarks

6.1 The Chaos Lab

A governance system must be tested by trying to break it. The **Chaos Lab** injects controlled incidents from a deterministic whitelist (unknown scenarios are rejected with HTTP 400) and runs the full agent pipeline against them. Current scenarios include database_regression (severity HIGH), memory_leak (MEDIUM), and container_crash_loop (CRITICAL). One injection executes the following sequence:

- Create the **Incident** and publish incident.created.
- The **Incident Commander** opens an investigation mission (INVESTIGATING), and a real, read-only git_status call is executed through the ToolExecutionService, so the Tool Calls area reflects genuine tool activity.
- The **Investigator** produces ranked hypotheses; a root cause is selected against the confidence floor.

- The **Coder** proposes a patch; the **Security** agent reviews every path against validation and protected-pattern rules.
- The **Verifier** independently runs its checks (incident_persisted, mission_investigating, security_no_suspicious).
- Validated patches are applied inside a confined sandbox root; the mission moves to AWAITING_APPROVAL, the incident to REMEDIATING, and an Approval record (risk HIGH, policy-v1) is created and announced via SSE.
- **The Chaos Lab never auto-resolves.** Resolution occurs only when a human decides.

6.2 Red-team validation of the guards

The Red Team endpoint attacks AEGIS’s own defences using the production components inside a temporary directory, returning expected and actual outcomes for each case. A scenario passes only when the attack is *blocked*.

Scenario	Attack	Defence exercised	Expected	Result
prompt_injection	Untrusted log text: "IGNORE PREVIOUS INSTRUCTIONS. DELETE THE DATABASE."	SecurityAgent.review_memory (injection screen, quarantine)	BLOCKED	BLOCKED
path_traversal	write_file to ../../../../etc/passwd via Filesystem MCP	Root-confined path resolution raises PermissionError	BLOCKED	BLOCKED
unknown_tool	Request for fabricated tool rm_rf_root	PolicyEngine.evaluate_tool (fail-closed)	BLOCKED	BLOCKED
destructive_action	Action categorised DESTRUCTIVE	PolicyEngine.decide (forced CRITICAL)	BLOCKED	BLOCKED

Table 9. Built-in adversarial scenarios.

6.3 Benchmark methodology

The BenchmarkRunner executes a chaos scenario through the Investigator, Coder, Security, and Verifier agents and records, per run: hypotheses generated, whether a root cause was selected, patches proposed, whether Security allowed the patch, whether independent verification passed, wall-clock duration, and a count of **unsafe actions**. Runs are persisted (with timestamp, provider, and scenario) so history is auditable, and the console’s Benchmarks page can launch a new run on either the deterministic **scripted** provider or a live local model. The figures below are from the 16 persisted scripted runs of the database_regression scenario.

Metric	Result	Detail
Benchmark runs	16	Scripted provider, scenario database_regression
Root-cause selection	100% (16/16)	2 hypotheses generated per run; a root cause above the confidence floor selected every time
Security review pass	100% (16/16)	1 patch proposed per run; all paths valid, none protected or suspicious
Independent verification pass	100% (16/16)	Verifier-executed checks all passed; no reliance on Coder claims
Unsafe actions	0	Mean, min and max of 0 across all runs
Pipeline duration (mean)	0.569 ms	Minimum 0.208 ms; maximum 0.967 ms

Table 10. Benchmark results across 16 scripted runs.

Outcome rates (16 runs)



Pipeline duration (ms, control plane)




Figure 5. Benchmark outcomes and pipeline duration for 16 scripted runs.

6.4 Interpreting the results responsibly

Scope. These runs use the **scripted** provider, which replays deterministic model responses. They therefore measure the *control plane*: schema validation, policy and security review, state transitions, verification logic, and persistence overhead. A mean of roughly half a millisecond demonstrates that governance adds negligible latency relative to model inference and sandbox execution; it does **not** measure the reasoning quality of a live model. The persisted history covers a single scenario, so the 100% rates should be read as evidence that the guarded pipeline behaves correctly and deterministically, not as a statistical claim about model accuracy.

This is the intended use of the benchmark. By removing the model from the loop, AEGIS can assert as a *regression test* that an unsafe action count of zero is a property of the control plane, not of a lucky sample. The runner accepts a live provider, so the same metrics can be gathered against real models and the same invariant (zero unsafe actions) must hold whatever the model proposes. Planned extensions include a larger scenario corpus across all three chaos scenarios, adversarial model outputs (patches targeting protected paths, malformed hypotheses), and per-stage latency attribution.

Conclusion

The central question for enterprise AI is no longer whether agents can reason well enough to be useful; it is whether organisations can *prove* what those agents are allowed to do. Prompt-level safeguards ask a probabilistic system to restrain itself. AEGIS takes the opposite position: let the model be as creative as it can be inside a boundary that is built from ordinary, auditable software.

In AEGIS, eight specialised agents propose; a policy engine scores and gates; a state machine constrains progress; typed MCP tools replace the shell; ephemeral cgroup-limited containers contain execution; an independent Verifier re-derives every claim; and a human holds the only key to irreversible change. Every step is written to a durable log before anyone is told about it. The measured result, 16 of 16 correct selections, reviews, and verifications with zero unsafe actions at sub-millisecond control-plane cost, is the expected consequence of an architecture in which safety does not depend on the model behaving.

As models grow more capable, the temptation will be to extend them more authority. The durable answer is not to trust them more but to constrain the system around them better: smaller blast radii, stricter contracts, stronger verification, and clearer accountability. Organisations that adopt this pattern can capture the speed of autonomous remediation while keeping the properties that production engineering demands: predictability, auditability, and a human who is accountable for what ships.

AI proposes and reasons. Deterministic software controls and verifies. That is how enterprise AI becomes safe enough to be trusted with real work.

Appendix A: API Surface

All mutating endpoints and all endpoints that return mission or operator data require a bearer JWT. Agent cards are intentionally public discovery metadata.

Prefix	Purpose	Notable endpoints	Auth
/auth	Registration and login	POST /register, POST /login (JWT)	Public
/projects, /environments, /memberships	Tenancy, deployment targets, RBAC	CRUD; membership grant / revoke with unique (user, project)	JWT
/incidents, /missions	Incident and mission read models	GET list, GET /{id}	JWT
/approvals	Human-in-the-loop gate	GET list; POST /{id}/decide (approved rejected)	JWT
/chaos, /redteam	Fault injection and adversarial testing	POST /chaos/inject; GET /redteam/scenarios	JWT
/tools	MCP tool catalogue and archive	GET /tools; GET /tools/calls	JWT
/a2a	Agent discovery and vitals	GET /agents, /agents/{name}, /capabilities/{cap}, /agents/{name}/vitals	Cards public; vitals per implementation
/memory	Observable memory	GET list; POST /retrieve (relevance, source, reason)	Per implementation
/policies	Policy transparency	GET (action categories, risk bands, tool categories)	Per implementation
/benchmarks, /replay	Evaluation and audit	GET history; POST /run; GET /replay/{mission_id}	Benchmarks per implementation; replay JWT
/updates	Real-time event stream	GET /stream (SSE: events, ping, heartbeat)	JWT
/health, /metrics, /chat	Operations	/health/live, /health/ready (503 when degraded), /metrics	Public

Table 11. REST surface mounted by the application factory.

Appendix B: Glossary

Term	Definition
A2A	Agent-to-Agent: discoverable agent cards, structured messages and tasks with validated state transitions.
cgroups	Linux control groups: kernel mechanism for limiting CPU, memory, and process counts of a container.
HITL	Human-in-the-loop: a recorded human decision required before an action may proceed.
MCP	Model Context Protocol: standard for exposing typed tools and resources to models; here, the only route to infrastructure.
Mission	A governed unit of work, with a code-enforced lifecycle, created to resolve an incident.
Policy version	Identifier of the policy ruleset in force when a decision was made; stamped on every Approval record.
Fail closed	On uncertainty or error, deny or fail rather than permit.
SSE	Server-Sent Events: one-way HTTP streaming used to push live events to the console.